

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 March 2001 (15.03.2001)

PCT

(10) International Publication Number
WO 01/18323 A1

(51) International Patent Classification⁷: E04F 15/024

(74) Agent: FARMER, James, L.; Speedfam-Ipec Corporation, 305 North 54th Street, Chandler, AZ 85226 (US).

(21) International Application Number: PCT/US00/21490

(22) International Filing Date: 7 August 2000 (07.08.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/391,113 7 September 1999 (07.09.1999) US

(71) Applicant (for all designated States except US): SPEEDFAM-IPEC CORPORATION [US/US]; 305 North 54th Street, Chandler, AZ 85226 (US).

(81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:


— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventors; and

(75) Inventors/Applicants (for US only): RAPISARDA, Joseph [US/US]; 500 N. Benson Lane, Chandler, AZ 85224 (US). COLLEY, Timothy [US/US]; 1375 W. Lisa Lane, Tempe, AZ 85284 (US).

(54) Title: CLEAN ROOM AND METHOD



(57) Abstract: A clean room which avoids the problems attendant with the raised floor found in prior art clean rooms uses a perforated floor upon which equipment can be directly placed. The perforated floor includes a regular array of openings through which air can pass to an underlying facility room. The openings are covered by a grate through which the air can pass. In combination the perforated floor and the grates are able to support equipment in any location thereon.



WO 01/18323 A1

CLEAN ROOM AND METHOD**BACKGROUND OF THE INVENTION**

5 This invention relates generally to a clean room, and more specifically to a floor for a clean room and to a method for establishing a clean room.

 Clean rooms are used extensively in the electronics industry and in other industries in which a clean, particle free environment is necessary during the fabrication or testing of a product. Clean rooms are rated by the number of particles of a given standard size that are
10 detected in a standard volume of air within the clean room. According to this rating system a "Class 10" clean room has only one-tenth the particle count of a "Class 100" clean room. Similarly, a "Class 1" clean room has only one-tenth the particle count of a "Class 10" clean room. The low particle count in a clean room is achieved by a large number of distributed air changes in the room. Air flows through the room, usually in a laminar fashion and usually
15 downwardly from the ceiling to the floor or to vents located near the floor. The air changes wash the particulate matter from the room. Other things being equal, the greater the number of air changes, the lower the particle count in the room. For example, a "Class 1" clean room usually requires more than 450 air changes per hour.

 Typically the air in a clean room enters the room through filters located in the ceiling,
20 passes through the room, washing over the contents of the room, and exits the room through openings or vents in a raised clean room floor to a plenum formed between the raised floor and the structural floor of the building. The air is then recirculated and again passes through the ceiling filters and into the room.

 Prior art clean rooms have all used a raised clean room floor. The raised and usually
25 perforated clean room floor is supported on a pedestal or plurality of pedestals. The pedestals are usually specially constructed structures designed specifically for the equipment that is to be placed on the raised floor. The raised floor itself is inadequate to support the weight of the equipment. The necessary pedestal is often very expensive, sometimes having a cost equaling a large percentage of the total equipment cost. The raised floor is necessary to form the return air
30 plenum and to provide a way to facilitate the equipment. Power lines, chemical lines, exhausts, drains, and the like pass through the raised floor and run under the raised floor to a facilities area. In addition, another reason for the widespread use of raised clean room floors, it is the desire, and often necessity, of suppressing vibrations caused by the equipment located in the clean room. Much of the processing that is done in the clean room requires a vibration free
35 environment as well as a particle free environment. The raised floor and the platform upon

which the raised floor is supported dampen vibrations that otherwise might be propagated by the underlying structural floor. A concrete slab floor has not been found satisfactory for a clean room environment because the slab tends to be a conduit for vibration.

In addition to the expense of the customized pedestal that must be used to support a raised
5 clean room floor, there are a number of other significant drawbacks to such a floor. Because the raised floor, by itself, is unable to support the weight of equipment that might be placed in the clean room, the raised floor also cannot support the weight of that equipment as it is moved into a clean room. This results in the necessity for disassembling the raised floor when
10 equipment is moved into a clean room or is moved about the clean room. The floor is disassembled, equipment is moved into the clean room, placed on the portion of the raised floor in substantially its final location, and then the remaining portion of the raised floor is reassembled. This activity compromises the cleanliness of the clean room every time a piece of equipment is moved into or is moved about the clean room. In addition, any facilities lines that
15 would be located under the portion of the raised floor that has to be removed will also be disturbed by the moving of equipment. Because of these difficulties, it is commonplace to build relatively small or compartmentalized clean rooms so that only a small area is contaminated by any moving process. This, of course, leads to disadvantages in terms of material flow because materials being processed must be moved into and out of these individual compartmentalized clean rooms.

20 In view of these and other problems with conventional clean room designs, it has been recognized that a need exists for a clean room that is less expensive than a raised floor clean room. There is also a need for a clean room that allows for non-intrusive clean room practices for facilitating equipment located in the clean room. The need also exists for a clean room that does not require an expensive and customized pedestal for equipment, but rather allows the
25 placement of equipment anywhere within a clean room. There is also a need for a clean room into which equipment can be moved and relocated without compromising the integrity of the clean room. A need also exists for a clean room that can be large in area and arbitrarily expandable in area.

BRIEF SUMMARY OF THE INVENTION

30 In accordance with one embodiment of the invention, a clean room is provided having a bearing floor capable of supporting equipment in any location thereon. The bearing floor is positioned over a facilities room which, in effect, is an extension of the clean room. The bearing floor has a regular array of openings through the floor which permit air to flow from the

clean room into the underlying facilities room. A wall structure is positioned on the bearing floor to surround a selected area of the bearing floor. A ceiling having a plurality of filtered air inlets is provided above the bearing floor and in contact with the top of the wall structure. A plurality of grates are positioned in those floor openings of the regular array that are located within the selected area bounded by the walls and solid, air impervious members are positioned in those floor openings of the regular array that are located outside the selected area. By changing air impervious members for grates, or vice versa, the area of the clean room can be expanded or reduced. Preferably the location and number of filtered air inlets is also adjusted to correspond to the number of grated openings in the clean room floor.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates, in plan view, a perforated clean room floor in accordance with one embodiment of the invention;

FIG. 2 illustrates, in cross-section, a clean room floor in accordance with the invention;

FIG. 3 illustrates, in cross-section, a portion of a clean room facility;

FIGS. 4 and 5 illustrate a grate and its method for installation in a perforated floor in accordance with one embodiment of the invention;

FIG. 6 illustrates schematically, in cross-section, a clean room facility in accordance with the invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

FIG. 1 illustrates, in plan view a floor 20 for a clean room in accordance with the invention. FIG. 2 illustrates a cross-section taken through the floor 20, as indicated, and FIG. 3 illustrates a further cross-section through floor 20 and the substructure, as indicated.

In accordance with one embodiment of the invention, as illustrated in FIGs. 1-3, the floor 20 is a poured in place concrete floor having a plurality of openings 22 extending through the thickness of the floor. Preferably the plurality of openings 22 are arranged in a regular array. The openings can be, for example, square openings having a side dimension of two feet with a spacing of two feet between openings. As will be explained below, each of the openings has a cover 24 inserted therein with the top of the cover co-planar with the top of the solid floor. The cover consists of either a grate or an air impermeable cover, depending upon the location within the clean room floor. Floor 20 is constructed overlying a room 30. Preferably room 30 is a below grade basement. Room 30 can be used advantageously to house facilities to be used by the equipment employed in the clean room. Accordingly, room 30 will be referred to herein as

a facility room. Room 30 includes, as illustrated in FIG. 3, bearing side walls 32 and a supporting concrete floor 34. A plurality of support pillars 36 extend upwardly from the concrete slab floor 34. A plurality of beams 38 span the facility room 30 and are supported by the plurality of columns 36. The support beams 38, in turn, support the perforated clean room floor 20. The facility room floor 34, walls 32, support pillars 36, beams 38, and floor 20 are preferably constructed of reinforced concrete. The composition of the concrete and the size and amount of rebar used for reinforcing are determined in accordance with standard structural calculations to support the weight of the equipment intended to be used in the clean room. Sound engineering practice, of course, dictates that the structure be overdesigned to support a weight much greater than that actually intended to be used in the clean room.

A preferred grate structure 50 to be used as one of the covers 24 inserted in an opening 22 in a clean room floor is illustrated in FIG. 4. FIG. 5 illustrates how that grate is held in place within the floor 20. Grate 50 includes a mesh top 52 and an apron 54 extending downwardly from at least two of the sides of the mesh top. Slots 56 are provided in the apron to allow adjustable attachment of the grate within opening 22 as will be explained below. The grates can be made of any suitable, structurally sound material. Preferably the grates are made of a metal such as stainless steel. The mesh top is designed to provide the free flow of air therethrough and simultaneously to provide structural strength. In accordance with one embodiment of the invention, the mesh top is fabricated from stainless steel and has openings of about 1 inch by 4 inches. The mesh top can be about 1½-2 inches in height and the apron is preferably about 4-5 inches in height.

FIG. 5, which illustrates a portion of floor 20 in cross-section, depicts a preferred method for attaching the grates within the openings 22. During the pouring of concrete floor 20, ferrule loops 60 are embedded in the solid portion 21 of floor 20. Preferably four ferrule loops are embedded in the walls of each of the openings 22, two each on opposing sides of the opening. The ferrule loops are positioned to align with slots 56 in the grates. A ferrule loop is used because the loop portion provides a good anchoring mechanism within the concrete material. The end of the ferrule loop extending out from the concrete is threaded to receive a bolt 62. The grate is placed in the opening so that the slots 56 in apron 54 are positioned over the threaded ends of ferrule loops 60. Bolts 62 are threaded onto the ferrule loops, the height of the grate is adjusted to be substantially co-planar with the surface of the concrete 21, and the bolts are tightened to hold the aprons and therefore, the grates securely in this aligned position.

The clean room facility, in accordance with the invention, is further illustrated schematically in FIG. 6. In this illustration the clean room facility is illustrated along a vertical

cross-section. The clean room facility includes facility room 30 as previously described. Overlying the facility room is a perforated floor 20. Vertical walls 70 surround an area of the perforated floor 20. The area of the perforated floor surrounded by walls 70 may encompass all of the perforated floor or, alternatively, a portion of the floor, leaving a second portion of the floor external to the walls 70. A ceiling 80 overlies perforated floor 20 including the portion of the perforated floor that is enclosed by walls 70. An airtight seal is made between the walls 70 and the ceiling 80 and also between the walls 70 and the perforated floor 20. Walls 70, a portion of ceiling 80, and a portion of perforated floor 20 thus enclose a volume constituting the clean room 90. Ceiling 80 includes a plurality of filtered air inlets 82. The filtered air inlets 82 have a greater density over the clean room 90 than they do over the area outside walls 70. In addition, the openings 22 which extend through floor 20 and which are located within the area bounded by walls 70 are covered by grates 50. The majority of the openings 22 through the floor 20 which are located outside the clean room 90 are covered by an area impervious cover 53.

Air circulation through the clean room facility is also illustrated in FIG. 6. Air enters clean room 90 through the filtered air inlets 82 as illustrated by arrows 84. The filtered air passes through clean room 90 and is exhausted into facility room 30 through the openings 22 in perforated floor 20 as illustrated by the arrows 86. Air is then exhausted from facility room 30 through an air plenum 88. A blower 92 conveys the air to a further plenum 94 which overlies ceiling 80. The air is then again filtered and forced through filtered air inlets 82. In this manner repeated air changes within clean room 90 "wash" particulate matter from the clean room. The number of air changes in clean room 90 is a function of the speed with which the air is circulated by blower 92, by the number of air inlets 82, and by the number of openings 22 through which the air can be exhausted into facility room 30. Because of the lower density of filtered air inlets in the region outside of walls 70 and because of the smaller number of openings 22 through which air can be exhausted, the particle count outside of clean room 90 will be greater than the particle count within the clean room.

The concept illustrated in FIG. 6 has a very important advantage over prior art clean rooms. A relatively large perforated floor 20 can be initially constructed over a relatively large facility room 30. Thereafter temporary walls 70 can be constructed on floor 20 to construct a clean room of any desired size up to and including a clean room encompassing all of floor 20. To change the size of clean room 90 requires only that the walls 70 be moved, the coverings on openings 22 be changed from air impervious to grates or vice versa, and the ceiling tiles be changed to increase or decrease the area of high density filtered air inlets.

Floor 20 is designed and constructed to be a load bearing floor. The floor is designed so that equipment can be placed directly on the perforated floor at any location within the clean room 90 regardless of the size of the clean room. Because equipment can be placed and supported anywhere on the perforated floor, equipment can be moved into and out of the clean room at will, and can be placed in any location within the clean room. Moving equipment into or about clean room 90 does not require the dismantling of a raised floor nor the assembly or moving of a costly support platform upon which the equipment must rest. Equipment can easily be moved into or out of clean room 90 on an air palette without compromising the cleanliness of the clean room. An air palette can easily move across the perforated floor by placing thin sheets of air impervious material such as thin sheets of plastic or metal over the floor grates as a temporary measure while the air palette passes over the grates.

In addition, all facilities lines such as gas lines, chemical lines, power lines, and the like can be routed from the equipment through the nearest opening 22 to the facilities room below. This is in contrast to the conventional raised floor clean room in which facilities lines are routed underneath the raised floor. Thus, in accordance with the invention, facilities lines need not be routed across the floor and thus need not impede the movement of equipment across the floor.

In a preferred method the clean room in accordance with the invention is constructed as follows. The facilities room 30 is first constructed in accordance with normal construction practices utilized in the building of fabrication facilities for the electronics and other similar industries. Preferably, facilities room 30 is constructed below grade and the floor and walls of the facility room are poured concrete constructed on substantial footings to minimize terrestrial vibration. Support pillars 36 and beams 38 are then erected in accordance with calculations done, as described earlier, on the size and reinforcing necessary to support the intended load. When properly designed in this manner, the perforated floor to be constructed overlying the beams can be extended to virtually any size by repeating the pattern of support pillars and beams. A clean room of any desired size can thus be constructed in this manner.

After the support pillars and beams are in place, temporary forms are erected over the beams. In accordance with a preferred embodiment the concrete forms for the perforated floor include a regular array of wooden boxes having the size desired for the openings in the floor. These wooden boxes can be made, for example, from plywood and are supported on or integral with the concrete forms. Ferrule loops 60 are attached to the wooden boxes for the ultimate attachment of the floor grates 50. With the forms including the wooden boxes in place, and with the appropriate amount of reinforcing rods in place, the perforated concrete floor is poured to a depth substantially co-planar with the tops of the array of wooden boxes. After the

concrete has set, the wooden boxes can be broken apart and removed leaving the ferrule loops in place in the edges of the openings through the concrete floor. In those areas which are not intended for immediate use as a clean room area, a temporary, air impervious cap can be placed in the openings 22. One way to form the air impervious caps, for example, is to pour about 4
5 inches of concrete in each of the openings that are not intended to receive a grate. Upon later expansion of the clean room, the 4 inches of concrete can easily be removed. Until so removed, however, the 4 inches of concrete is adequate to provide a safe floor upon which foot traffic and some equipment can be moved. Alternatively, temporary air impervious caps can be placed in those openings which are not initially intended to receive a grate. Temporary caps can be made
10 from concrete, solid pieces of metal, or the like. Such caps can also be affixed to the ferrule loops.

One difficulty with solid concrete floors in a fabrication area is that vibrations tend to propagate along a concrete slab. Thus vibration generated by one piece of equipment may adversely affect the performance of an adjacent piece of equipment. It has been discovered,
15 however, that the perforated floor in accordance with the invention does not have this problem of easy propagation of vibrations. Instead, it has been discovered that the perforated floor in accordance with the invention serves to dampen vibrations.

Although not illustrated in any of the figures, one further embodiment of the invention includes the incorporation of adjustable louvers in the metal grates 50. Such adjustable louvers
20 allow for adjusting the air flow through the clean room facility.

Thus it is apparent that there has been provided, in accordance with the invention, a clean room facility and a method for its fabrication that overcomes the disadvantages of prior art clean rooms. Although the invention has been described and illustrated with respect to specific illustrative embodiments thereof, it is not intended that the invention be limited to these
25 illustrative embodiments. For example, those of skill in the art will recognize that other building materials and dimensions can be substituted for those set forth in the specific examples given above. For example, the size and spacing of the openings through the floor can be changed to accommodate particular clean room layouts or particular equipment. Likewise, different forms or shapes of the grates can be utilized as would be obvious to those of skill in
30 the art. Accordingly, it is intended to encompass within the invention all variations and modifications as fall within the scope of the appended claims.

CLAIMS

What is claimed is:

1. A flooring structure for a clean room comprising:
a facilities room having a concrete slab floor;
5 a plurality of support pillars extending above said slab floor;
a plurality of beams supported by said pillars;
a solid, poured in place, bearing floor having a plurality of openings therethrough to allow
the flow of air from a clean room located above said floor to said facilities room located below
said floor, said floor being able to support equipment at any location thereon; and
10 a plurality of grates positioned in said openings.
2. A clean room facility comprising:
a facilities room;
a bearing floor positioned over said facilities room and capable of supporting equipment
at any location thereon;
15 a regular array of openings in said bearing floor through which a flow of air can pass to
said facilities room;
a wall structure positioned on said bearing floor to surround a selected area on said
bearing floor;
a ceiling above said wall structure having a plurality of filtered air inlets therein; and
20 a plurality of grates positioned in a portion of said regular array of openings located
within said selected area.
3. The clean room facility of claim 2 further comprising: a plurality of solid, air
impervious members positioned in a second portion of said regular array of openings located
outside said selected area.
- 25 4. The clean room facility of claim 3 wherein said solid, air impervious members
comprise poured concrete.
5. The clean room facility of claim 3 wherein said solid, air impervious members
have a top surface substantially coplanar with the upper surface of said bearing floor.
6. The clean room facility of claim 3 wherein said ceiling comprises a first density
30 of filtered air inlets in the portion of said ceiling above said selected area and a density of
filtered air inlets lower than said first density in the portion of said ceiling above an area outside
said selected area.
7. The clean room facility of claim 2 wherein said wall structure is capable of being

relocated to change the size of said selected area.

8. The clean room facility of claim 2 wherein selected ones of said openings can be selected for the routing of facilities lines between equipment positioned on said bearing floor and said facilities room.

5 9. The clean room facility of claim 2 further comprising air circulating equipment capable of causing the flow of air through said first density of filtered air inlets, through said plurality of grates, and into said facilities room.

10 10. The clean room facility of claim 9 wherein said facilities room is a plenum for the recirculation of said air to said air circulating equipment.

10 11. The clean room facility of claim 2 wherein said plurality of grates comprise metal grates comprising a louver adjustable for the control of air therethrough.

12. The clean room facility of claim 11 wherein said plurality of grates further comprises an adjustment mechanism for adjusting the height of said grate relative to the top surface of said bearing floor.

15 13. A method for fabricating a clean room facility comprising the steps of:
constructing a first room having a structurally solid floor;
forming a plurality of support pillars extending above said solid floor;
providing a plurality of beams spanning said support pillars, said support pillars and said beams designed to provide a low vibration environment for equipment to be located in said
20 clean room facility;

providing concrete forms for the pouring of a concrete floor overlying said beams, said forms comprising a regular array of demountable boxes upstanding from a surface of said forms;

25 pouring a concrete floor overlying said beams, the upper surface of said concrete floor being substantially coplanar with the upper surface of said demountable boxes;

removing said demountable boxes to leave a concrete floor having a regular array of openings therethrough;

erecting walls surrounding an area on said concrete floor;

30 constructing a ceiling overlying said concrete floor, said ceiling having a plurality of filtered air inlets therethrough and forming an air tight seal with said walls; and

providing an air recirculation system to circulate air through said filtered air inlets, through said plurality of openings, into said first room, and back to said filtered air inlets.

14. The method of claim 13 further comprising the step of providing a temporary

solid cover for a portion of said array of openings positioned outside said area.

15. The method of claim 13 wherein said step of providing a temporary solid cover comprises pouring a concrete cover.

16. The method of claim 13 further comprising the step of inserting a grate into a second portion of said array of openings positioned inside said area.

17. The method of claim 16 wherein said step of inserting comprises anchoring a plurality of ferrule loops in the walls of said openings and bolting grates to said ferrule loops.

18. The method of claim 13 wherein said step of constructing a ceiling comprises the steps of providing a first density of filtered air inlets overlying said area and providing a second, lower density of filtered air inlets overlying portions of said floor outside said area.

19. The method of claim 13 further comprising the step of routing facilities through selected ones of said regular array of openings from said first room to locations above said concrete floor.

20. A clean room comprising:
an enclosed space;
a bearing floor dividing the enclosed space into a first clean portion and a second facilities portion, the bearing floor capable of supporting processing equipment at any location thereon;
a plurality of apertures in the bearing floor through which air can pass from the first clean portion to the second facilities portion;
a filtered air inlet capable of introducing clean air into the first clean portion; and
an air handler capable of circulating air from the second facilities portion, through the filtered air inlet to the first clean portion.

21. The clean room of claim 20 wherein the bearing floor comprises reinforced concrete.

22. The clean room of claim 21 wherein the bearing floor comprises poured in place reinforced concrete.

23. The clean room of claim 20 further comprising grates positioned in the apertures and capable of allowing the passage of air therethrough from the first clean portion to the second facilities portion.

24. The clean room of claim 23 wherein the grates comprise metal fixtures having an upper surface substantially coplanar with the upper surface of the bearing floor.

25. The clean room of claim 20 wherein the enclosed space comprises a volume bounded by the bearing floor, a ceiling, and temporary wall structures extending from the bearing floor to the ceiling.

26. The clean room of claim 25 wherein the temporary wall structure partitions off a selected portion of the first clean portion.

27. The clean room of claim 26 wherein the filtered air inlet comprises a plurality of apertures in the ceiling.

28. The clean room of claim 27 wherein the plurality of apertures in the ceiling has a greater density within the selected portion of the first clean portion compared to the density outside the selected portion.

29. The clean room of claim 27 wherein the plurality of apertures in the bearing floor has a greater density within the selected portion of the first clean portion compared to the density outside the selected portion.

30. A method for facilitating a clean room comprising the steps of:
providing a bearing clean room floor capable of supporting processing equipment at any location thereon, the bearing floor comprising a plurality of openings therethrough capable of exhausting air from the clean room to a space immediately below the clean room;

transporting a piece of processing equipment across the bearing clean room floor to a predetermined location; and

placing the piece of processing equipment directly on the bearing clean room floor at the predetermined location.

31. The method of claim 30 wherein the step of transporting comprises transporting the piece of processing equipment on an air pallet.

32. The method of claim 30 wherein the step of transporting comprises transporting the piece of processing equipment across at least one of the plurality of openings.

33. The method of claim 32 wherein the step of transporting further comprises the step of placing a substantially air impervious material over the opening.

34. The method of claim 33 wherein the step of transporting comprises placing a thin sheet comprising metal or plastic over the opening.

35. The method of claim 30 further comprising the step of routing a facility line from the piece of processing equipment, through one of the plurality of openings to the space below the clean room.

36. The method of claim 30 wherein the step of transporting is performed without dismantling any of the bearing clean room floor.

37. A method of providing filtered air to a clean room comprising the steps of:

providing a bearing clean room floor capable of supporting equipment at any location thereon, the floor having a plurality of openings therethrough;

providing a clean room ceiling overlying the floor and having a plurality of filtered air inlets therein;

introducing air into the clean room through the plurality of filtered air inlets;

passing the air through the clean room and withdrawing the air from the clean room through the plurality of openings in the floor;

passing the air withdrawn through the plurality of openings to a plenum below the clean room floor;

withdrawing the air from the plenum through a return air duct; and

returning the air withdrawn from the plenum to the filtered air inlets.

38. A clean room comprising:

a first room defined by a floor and a wall structure surrounding said floor;

a second room positioned over said first room, said second room being defined by a floor having a plurality of openings therethrough and a wall structure surrounding said floor;

a ceiling having a plurality of filtered air inlets positioned over said second room; and

at least one air plenum located near an outer perimeter of said first room for returning air to said filtered air inlets.

39. The clean room of claim 38 wherein the floor of said second room comprises a load bearing, concrete floor.

40. The clean room of claim 38 wherein the floor of said second room comprises a solid, poured in place, bearing floor capable of supporting equipment at any location thereon and said plurality of openings comprise a regular array of openings having at least one of a grate or a solid, air impervious member positioned therein.

41. The clean room of claim 40 wherein said grates and said solid, air impervious members are removable so that one may vary the plurality of openings in the floor of said second room.

42. The clean room of claim 40 wherein said solid, air impervious members are comprised of concrete.

43. The clean room of claim 40 wherein a top surface of each of said solid, air impervious members lies substantially co-planar with an upper surface of the floor of said second room.

44. The clean room of claim 40 wherein each of said grates includes a louver for adjusting air flow through each of said grates.

45. The clean room of claim 38 wherein facilities used by equipment located within the second room are housed within the first room.

46. The clean room of claim 45 wherein lines for connecting the facilities to the equipment are routed through the plurality of openings in the floor of said second room.

47. The clean room of claim 38 further comprising a plurality of support pillars extending from the floor of said first room to the floor of said second room.

48. The clean room of claim 47 further comprising a plurality of beams located beneath the floor of said second room, said plurality of beams being supported by said plurality of support pillars.

49. The clean room of claim 38 further comprising a wall structure located within said second room, to create an additional room having a same floor and ceiling as said second room

50. The clean room of claim 38 wherein said plurality of filtered air inlets comprise various densities of filtered air inlets located within a surface area of said ceiling.

51. The clean room of claim 38 further comprising at least one blower to direct a flow of air through said filtered air inlets in said ceiling, through the plurality of openings in the floor of said second room and into said at least one air plenum for return to said filtered air inlets.

52. The clean room of claim 38 further comprising an air plenum located above said ceiling.

53. The clean room of claim 45 wherein said first room functions as an air plenum positioned beneath the floor of said second room.

54. A cleaning room floor structure comprising:

a facilities room having facilities housed therein wherein said facilities room has a solid, air impervious floor;

a solid, load bearing floor positioned above and acting as a ceiling for said facilities room; said load bearing floor having a plurality of openings therethrough to allow

air flow from a clean room above said load bearing floor to the facilities room below the load bearing floor; and

at least one of a grate or a solid, air impervious element positioned in each of said plurality of openings.

1/5




FIG. 1

2/5




FIG. 2




FIG. 3

3/5




FIG.4

4/5




FIG.5

5/5




FIG. 6

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 00/21490

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 E04F15/024

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E04F F24F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 012, no. 484 (M-776), 16 December 1988 (1988-12-16) & JP 63 201441 A (FUJITSU LTD;OTHERS: 01), 19 August 1988 (1988-08-19) abstract	20, 37, 38
A		1-3, 5-7, 9, 10, 13, 16, 18, 19, 23-28, 39-41, 47-54
	---	-/--

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

16 November 2000

Date of mailing of the international search report

24/11/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Ayiter, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/21490

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 699 640 A (SUZUKI MASAMI ET AL) 13 October 1987 (1987-10-13) the whole document	37, 38
A		1-11, 20, 21, 23, 25-29, 39-43, 49-52, 54
A	EP 0 079 066 A (GUTERMUTH PAUL ;OETJEN HEINRICH (DE)) 18 May 1983 (1983-05-18) page 10, line 21 -page 21, line 30; figures 1-5	1-3, 5, 13, 20, 23, 24, 30, 37
A	US 5 518 451 A (RENZ MANFRED ET AL) 21 May 1996 (1996-05-21) column 4, line 3 -column 7, line 67; figures 1-4	1, 2, 8-10, 13, 18-21, 23, 37, 38, 47, 51, 52
A	DE 38 32 915 A (GABLER MARTIN) 29 March 1990 (1990-03-29) column 2, line 61 -column 8, line 22; figures 1-13	1, 2, 7-11, 20, 23-27, 30, 37

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 00/21490

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 63201441 A	19-08-1988	JP 2115855 C JP 8027042 B	06-12-1996 21-03-1996
US 4699640 A	13-10-1987	JP 62005031 A DE 3621452 A GB 2177501 A,B	12-01-1987 08-01-1987 21-01-1987
EP 0079066 A	18-05-1983	DE 3144815 A AT 19283 T	26-05-1983 15-05-1986
US 5518451 A	21-05-1996	DE 4328995 A DE 59405568 D EP 0641977 A ES 2115120 T	02-03-1995 07-05-1998 08-03-1995 16-06-1998
DE 3832915 A	29-03-1990	NONE	